



CERTIFICATE

No. Z2 099333 0045 Rev. 14

Holder of Certificate: LONGi Green Energy Technology Co., Ltd.

No. 388, Middle Hangtian Road

Chang'an District

710100 Xi'an City, Shaanxi

PEOPLE'S REPUBLIC OF CHINA

Certification Mark:



Product: Crystalline Silicon Terrestrial Photovoltaic (PV) Modules

Mono-Crystalline Silicon Photovoltaic Module

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition, the certification holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the testing and certification regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 704061700516-14

Valid until: 2026-01-26

Date, 2021-01-27

gatio

(Zhulin Zhang)



CERTIFICATE

No. Z2 099333 0045 Rev. 14

LR6-72HV-xxxM, (xxx=335-360 in step of 5) Model(s):

LR6-60HV-xxxM, (xxx=280-300 in step of 5)

LR6-72PH-xxxM, (xxx=340-380 in step of 5)

LR6-60PH-xxxM, (xxx=285-315 in step of 5)

LR6-72HPH-xxxM, (xxx=365-395 in step of 5)

LR6-72HIH-xxxM, (xxx=365-395 in step of 5)

LR6-60HPH-xxxM, (xxx=300-325, in step of 5)

LR6-60HIH-xxxM, (xxx=300-325 in step of 5)

LR6-72OPH-xxxM, (xxx=385-415 in step of 5)

LR6-60OPH-xxxM, (xxx=335-365 in step of 5)

LR6-72HPH-xxxMC, (xxx=375-390 in step of 5)

LR6-60HPH-xxxMC, (xxx=305-325 in step of 5)

LR6-60ZPH-xxxM, (xxx=330-355 in step of 5)

LR4-72HPH-xxxM, (xxx=420-465 in step of 5)

LR4-72HIH-xxxM, (xxx=420-465 in step of 5)

LR4-60HPH-xxxM, (xxx=350-380 in step of 5)

LR4-60HIH-xxxM, (xxx=350-380 in step of 5)

LR4-72ZPH-xxxM, (xxx=420-435 in step of 5)

LR4-60ZPH-xxxM, (xxx=350-365 in step of 5)

LR4-78ZPH-xxxM, (xxx=455-485 in step of 5)

LR5-72HPH-xxxM, (xxx=525-555 in step of 5)

LR5-66HPH-xxxM, (xxx=480-505 in step of 5)

LR4-66HPH-xxxM, (xxx=395-415 in step of 5)

LR4-66HIH-xxxM, (xxx=395-415 in step of 5)

LR5-72HIH-xxxM, (xxx=525-545 in step of 5)

LR5-66HIH-xxxM, (xxx=480-500 in step of 5) xxx is standing for rated output power at STC

Parameters:

Fire Safety Class: Class C according to UL790.

Safety Class: Class II Max. System Voltage: 1500V DC

Test Laboratory: Yangzhou Opto-Electrical

Products Testing Institute.

No.10 West Kaifa Road, Yangzhou

225009 Jiangsu, P.R. China.

Construction: Framed, with Junction box,

cable and connector.

Tested according to: IEC 61215-1:2016 IEC 61215-1-1:2016

IEC 61215-2:2016

IEC 61730-1:2016

IEC 61730-2:2016

EN 61215-1:2016

EN 61215-1-1:2016

EN 61215-2:2017

EN IEC 61730-1:2018

EN IEC 61730-1:2018/AC:2018-06

EN IEC 61730-2:2018

EN IEC 61730-2:2018/AC:2018-06