Ezlink

Ezlink3000 features compact size, lightweight design, and installation flexibility. With WiFi and LAN compatibility, Ezlink makes it possible for inverters to be connected to the GoodWe Smart Energy Management System (SEMS) for data monitoring. Ezlink3000 provides paralleling function for compatible inverters. Additionally, it can be used outdoors freely with its ability to accommodate harsh working conditions, thanks to a wide range of working environment temperatures and humidity.



- Parallel function
- Master and Slave connectivity
- Extensive communication methods: Wi-Fi, LAN
- Powerful protocol compatibility
- Safe asymmetric encryption
- Recordable operation logs

Model	Ezlink3000
General Data	
Connection Interface	USB
Ethernet Interface	10 / 100Mbps self-adaption, Communcation distance ≤100m
Installation	Plug and Play
Indicator	LED Indicator
Dimensions (W × H × D mm)	48 × 153 × 32
Weight (g)	130
Power Consumption (W)	≤2W (typical)
Wireless Parameter	
Bluetooth Communication	Bluetooth 5.1
WiFi Communication	802.11 b / g / n (2.412GHz - 2.484GHz)
Operating Mode	STA
Environment	
Operating Temperature Range (°C)	-30 ~ +60
Storage Temperature Range (°C)	-30 ~ +70
Relative Humidity	0 - 100% (non-condensing)
Ingress Protection Rating	IP65
Max. Operating Altitude (m)	4000

*: Please visit GoodWe website for the latest certificates.

GoodWe-Single page-20241107-EMEA-EN-V2.1. Information may be subject to change without notice during product improving.