GOODWE



SMART METER

GoodWe's Smart Meter is designed with high-precision small-scale dimensions, and convenient operation and installation. It is available for both single-phase and three-phase grid system connection to detect voltage, current, power and energy, and for working with inverters including SEMS systems for the purpose of energy management.

- Modular Design
- Precise Data Collection
- Easy Installation
- CTs included

Model			GM1000	GM1000D	GM3000
Input	Grid		Single-phase	Single-phase	Three-phase
	Voltage	Nominal Voltage-Line to N (Vac)	110 / 230	110 / 230	230
		Nominal Voltage-Line to Line (Vac)	-	-	400
		Voltage Range	0.88Un-1.1Un		
		Nominal AC Grid Frequency (Hz)	50 / 60		
	Current	Current Transformer Ratio	120A:40mA		
		Number of Current Transformers	1	2	3
Communication			RS485		
Communication Distance (m)			1000		
User interface			3 LED, Reset button		
Accuracy	Voltage / Current		Class 1		
	Active Energy		Class 1		
	Reactive Energy		Class 2		
Power Consumption (W)			<3		
Machanical	Dimensions (W × H × D mm)		36 × 85 × 66.5		
	Housing		2 modules		
	Weight (g)		250	360	450
	Mounting		Din rail		
Environment	Ingress Protection Rating		IP20		
	Operating Temperature Range (°C)		-25 ~ +60		
	Storage Temperature Range (°C)		-30 ~ +70		
	Relative Humidity (non-condensing)		0 ~ 95%		
	Max. Operating Altitude (m)		2000		

*: Please visit GoodWe website for the latest certificates.

GoodWe-Single page-20230328-EN-V2.1. Information may be subject to change without notice during product improving.