Growatt ShineGPRS-X

- Plug and play
- Built-in memory for up to one month of data
- Remote online monitoring and maintenace
- Support more than 100 telecommunication



POWER-ING TOMO-RROW

GROWATT

www.growatt.com

Datasheet	ShineGPRS-X
Wireless parameters	
Network type	GSM/GPRS
GSM/GPRS/EDGE frequency range	850/900/1800/1900MHz
Rated power	GSM850/GSM900：2W DCS1800/PCS1900：1W
Hardware parameters	
Serial port speed	9600bps/115200bps
Operating voltage	5V(±5%)
Operating current	2A
Rated power	5W
Operating temperature	-30°C ... +65°C
Protect degree	IP65
Application parameters	
Servers	ShineServer
Communication with Inverter	USB(Modbus RTU protocol)
Communication with server	TCP(Modbus TCP protocol)
Configuration interface	APP
SIM card type	Standard SIM card
Data transmission interval	5 Minutes
Default server IP	server.growatt.com
General data	
Dimensions(L/H/W)	122/32/47mm
Weight	70g
Language	English,Chinese
Warranty	1 year
	CE

SHENZHEN GROWATT NEW ENERGY CO.,LTD. A: 4-13/F,Building A,Sino-German(Europe)Industrial Park,Hangcheng Ave,Bao'an District,Shenzhen,China
T: + 86 755 2747 1900 F: + 86 755 2749 1460 E: info@ginverter.com